


## Hybrid aluminum electrolytic capacitor ▲ 125°C

### AVMC Series


- ▲ 22 $\mu$ F to 470 $\mu$ F ▲ 25V<sub>DC</sub> to 80V<sub>DC</sub>
- ▲ Long lifetime with 4000h endurance at 125°C
- ▲ Very low leakage current and self-healing of dielectric layer
- ▲ Low drift and stable electrical characteristics over lifetime



## High voltage solid electrolytic capacitor ▲ 105°C

### ARHA Series

- ▲ 22 $\mu$ F to 1500 $\mu$ F ▲ 25V<sub>DC</sub> to 100V<sub>DC</sub>
- ▲ High ripple current up to 5.3A at 100kHz/105°C
- ▲ No liquid electrolyte ▲ No dry-out effect
- ▲ Ultra long lifetime with 5000h endurance at 105°C



when experience meets **know-how**





Manufacturer Group of Technology

[www.mgt.co.com](http://www.mgt.co.com) ▲ [sales@mgt.co.com](mailto:sales@mgt.co.com)

## Stacked solid electrolytic capacitor ▲ 125°C

### ACTH Series

- ▲ 15 $\mu$ F to 330 $\mu$ F ▲ 2.5V<sub>DC</sub> to 25V<sub>DC</sub>
- ▲ Ultra-low ESR up to 6m $\Omega$  at 100kHz/20°C
- ▲ No liquid electrolyte ▲ No dry-out effect
- ▲ Low height with 1.9mm ideal for space critical applications



## High ripple solid electrolytic capacitor ▲ 105°C

### AREC Series

- ▲ 270 $\mu$ F to 2200 $\mu$ F ▲ 2.5V<sub>DC</sub> to 16V<sub>DC</sub>
- ▲ High ripple current up to 6.6A at 100kHz/105°C
- ▲ Low drift and stable electrical characteristics over lifetime
- ▲ No electrolyte ▲ No dry-out effect



when experience meets **know-how**



Manufacturer Group of Technology

[www.mgt.co.com](http://www.mgt.co.com) ▲ [sales@mgt.co.com](mailto:sales@mgt.co.com)